

FITMENT OF WIPER MOTOR AII7M0I03F (LHD) OR AII7M0I04F (RHD)
TO ELISE 'MK.1' OR EARLY 'MK.2'

Elise 'Mk.1' and early 'Mk.2' cars used a wiper motor assembly featuring a fabricated mounting bracket, and a female threaded spindle for the wiper arm. Later motor assemblies, feature pressed brackets and a male threaded spindle. If a later type motor assembly is to be fitted in place of an earlier version, the vehicle harness connector plug must be cut off, and the wires reterminated and inserted into the new connector plug, using the parts supplied and instructions below.

1. Cut the five cables on the vehicle harness as close to the wiper connector block as possible.
2. Reterminate each cable with a new terminal supplied.
3. Insert the cables into the new connector block supplied in the following order (counting from any end):
 - Black*
 - Brown/Light Green*
 - Green*
 - Blue/Light Green*
 - Red/Light Green*Note that although the connector block has orientation features, the block may be inserted into the motor connector either way up to accommodate RHD and LHD variants.
4. On both RHD and LHD cars, fit the harness connector to the motor such that:
 - Red/Light Green harness cable mates with the Green motor cable;
 - Blue/Light Green harness cable mates with the Red motor cable.
5. Use the new nut supplied to attach the wiper arm to the wheelbox spindle.